

Technical data sheet

Type FIX MATIC 548

Air purger

Applications and special features



- Air purger for heating
- Removable isolation valve
- Purger plug
- Before any use, please unscrew the purger plug half a turn to release any air.

Technical description

DN	Weight	References	Vvs-nr
3/8"	110g	149B 5106	

- **Connection** : Male 3/8" G
- **Permissible operating pressure PFA water** : 10 bar
- **T°** : Mini. 0 °C
Maxi. 110 °C
- **Permissible fluids** : Clear water

Overall dimensions

Description	Materials
CASING	Brass
COVER	Brass
FLOAT	Plastic
ISOLATION VALVE	Brass



Danfoss can accept no responsibility for possible errors in catalogue, brochures and other printed material. Danfoss reserve the right to alter its products without notice. This also applies to products already agreed. All trademarks in this material are the property of the respective companies. Danfoss and the logo type are trademarks of Danfoss A/S. All right reserved.



Danfoss Socla

365 rue du lieutenant Putier
71530 VIREY LE GRAND
Postal address : BP273
71107 CHALON SUR SAONE Cedex

Tel : 33 3 85 97 42 52
Fax : 33 3 85 97 97 42
<http://www.danfoss-socla.com>
e-mail: commerfr@danfoss.com